METHOD AND SYSTEM FOR OPTICAL ROUTING OF

VARIABLE-LENGTH PACKET DATA

CROSS-REFERENCE TO RELATED APPLICATIONS

This is the first application filed for the present invention.

MICROFICHE APPENDIX

Not Applicable.

TECHNICAL FIELD

The present invention relates to optical communications networks, and in particular to a method and system for optical routing of variable length packet data across an optical communications network.

BACKGROUND OF THE INVENTION

Optical communications networks have recently become established as the preferred backbone for data communications because of the high bandwidth capacity of the optical fiber links. Concurrently, the internet protocol (IP) is gaining popularity for controlling the routing of packetized data across a communications network. Typically, IP packets are converted into optical form and launched into a fiber optic link towards a node of the network. When the optical signal arrives at the node, it is usually converted back into electronic form and buffered to allow the header portion of the IP packet to be extracted and decoded to determine the routing for the next hop towards the destination.

This solution suffers the disadvantage that within each node of the optical network, the IP packet must be converted from optical to electronic form and then back into optical form for transmission over the next link.

5   Thus, while the bandwidth capacity of each fiber link may be very high, the overall bandwidth capacity of the network is restricted by the speed and reliability of the electronic components of each node, and in particular the speed with which optical signals can be converted into

10   electronic signals and buffered. United States Patent No. 5,617,233, issued to Boncek on April 1, 1997, proposes a solution to this problem by providing a transparent optical node structure for use in a two-connected optical packet switching architecture. According to Boncek, each

15   packet is separated into its respective header and payload portions. The header portion is transmitted over a link on one wavelength (or channel) and the data portion of the packet is transmitted on a second wavelength. Accordingly, at each node it is only necessary to electronically decode

20   the header portion of the packet, which can be easily detected independently of the data portion of the packet. The decoded header portion can then be used to determine packet routing in a conventional manner, and this routing information is used to control a transparent optical switch

25   to guide the data portion of the packet through the transparent optical switch and into a downstream link without being converted into an electronic signal and back again to an optical signal. Optical buffering of the data portion of the packet (e.g. by use of one or more fiber

30   rings having a predetermined length) is used to ensure proper timing between the header and data portions of each

packet, and may also be used to resolve contention issues and provide add/drop functionality of the node.

Known methods of buffering (or delaying) optical signals rely on the use of optical fiber rings or the like having a predetermined length. An optical signal can therefore be delayed for a period of time by launching the signal into the fiber ring. According to Boncek, such a ring is used on the input side of each node to delay the data portion of the packet for a period of time sufficient to allow the header portion to be decoded and the transparent optical switch set to provide routing of the data portion through to the appropriate output node. The delay loop on the input side of the node can also be adjusted to compensate for known differences in the propagation speed of the header and data portions of the packet through the link. A further delay ring can also be used within the transparent optical switch to resolve contention issues by enabling a data portion of a packet to be delayed by a period of time equivalent to the length of a data packet arriving on another input node, to thereby enable that other data packet to clear an output port before the first data packet arrives at that same output port.

The use of a fiber ring for delaying and buffering optical signals suffers the disadvantage that the amount of delay is governed primarily by the length of the fiber ring (the time delay is equal to the length of the ring divided by the speed of light in the fiber medium of the ring). This is generally fixed during the design and construction of the fiber ring, and cannot be varied during operation of the node. Because contention resolution requires one data

packet to be delayed by a period of time equal to or greater than the length of a second data packet, assumptions must be made concerning the maximum allowable packet length during the design phase of the node.

5   Successful operation of the network depends on the data packets never being longer than the previously defined maximum allowable length. If the defined maximum length is too large, unnecessarily long delays will be incurred as packets move through the node. Alternatively, if the

10   defined maximum length is too small, the available band-width of the network may be unnecessarily limited.

Boncek's use of delay rings at the input of the network node imposes a further restriction that the size and content of the packet header must also be predetermined

15   at the time of design and construction of the node, because the header portion must be fully decoded and interpreted before the delayed data portion arrives at the transparent optical switch. In light of the foregoing, it will be apparent that the transparent optical node structure of

20   Boncek will only work in a network environment in which data packets of a uniform predefined size and format are employed.

However, in the modern network space, packetized data traffic of multiple different protocols (e.g. internet

25   protocol, asynchronous transfer mode, etc.) is transported over a common network infrastructure. Each protocol provides its own packet (or frame) size and format standards. Additionally, some protocols (e.g. IP) are specifically designed to allow packets having widely

30   varying lengths. New routing protocols, for example the multi protocol label switching (MPLS) protocol have been

proposed to facilitate multi-protocol traffic across a common network infrastructure. Such routing protocols are commonly derived from the internet protocol, and are also specifically designed to handle data packets having widely
5   differing format and size.

Accordingly, a system enabling full optical routing of variable length packetized data traffic across a communications network remains highly desirable.

SUMMARY OF THE INVENTION

10   An object of the present invention is to provide a method and system enabling full optical routing of variable length packetized data across an optical communications network.

Another object of the present invention is to
15   provide an optical communications system in which variable length packetized data is optically routed across the communications system within fixed length data frames.

A still further object of the present invention is to provide an optical communications system in which
20   variable length data packets are optically routed across the communications system on the basis of routing information encoded within a label block which is independent of the format of the variable length data packet.

25   A still further object of the present invention is to provide an optical communications system in which routing information of a data frame is encoded within a label block that is transported across the communications

system on a predetermined label channel, and a variable length data packet is inverse multiplexed and transported across the communications system on a plurality of separate data channels.

5   Accordingly, an aspect of the present invention provides a method of routing variable-length packet data across a communications network having a plurality of data communications channels. A data packet is inverse-multiplexing into a frame comprising: a label block

10   containing label information of the frame; and two or more respective payload blocks having a predetermined length. The label block is transmitted over a label channel of the communications network. Each payload block is transmitted over respective separate data channels of the

15   communications network.

Another aspect of the present invention provides a communications network adapted for communication of variable length data packets. The communications network comprises: an interface for inverse-multiplexing a data

20   packet into a frame having a label block containing label information of the frame, and two or more respective payload blocks having a predetermined length; a first optical coupler for transmitting the label block over a label channel of the communications network; and a

25   respective second optical coupler for transmitting each payload block over a respective separate data channel of the communications network.

A further aspect of the present invention provides a router for routing packet data traffic between a first

30   and a second link of a communications network adapted for

communication of data packets having a variable length.
The data packets are transported within data frames
comprising a label block and two or more payload blocks
having a predetermined length. The label block is carried
5   on a label channel of the communications network, and the
payload blocks are carried on respective data channels of
the communications network. The router comprises: at least
one input port connected to the first link for receiving
sequential frames; at least one output port connected to
10   the second link for sending sequential frames; a label
decoder adapted to decode a label block received over the
label channel through the input port; a switch controller
responsive to the label decoder to generate a routing
control signal indicative of a selected output port; a
15   transparent optical switch responsive to the routing
control signal to establish a transparent optical path
between the input port and the selected output port; and a
label regenerator adapted to regenerate the label block for
sending over the label channel through the selected output
20   port.

The communications network may be a wave division
multiplex (WDM) optical network. Preferably, the
communications network is adapted for multi-protocol label
switched (MPLS) routing of the packet data traffic. The
25   packet data traffic may include any one or more of internet
protocol (IP) packets having a variable length, and
asynchronous transfer mode (ATM) frames.

A number N of payload blocks, and the predetermined
length of each payload block of each frame can be selected
30   based on an expected mean length of the data packets, or
may be selected based on other criteria. In either case,

inverse-multiplexing a data packet preferably includes dividing the data packet into N packet segments of substantially equal length. When the length of each packet segment is less than or equal to the length of each payload

5   block, each packet segment can be buffered for transmission within a respective payload block of a frame.

Alternatively, when the length of each packet segment is greater than the length of each payload block, each packet segment may be subdivided into two or more

10   portions, each portion having a length equal to or less than the length of a payload block. Each portion may then be buffered for transmission within a respective payload block of respective successive frames. By this means, a large data packet can be subdivided into two or more

15   portions and transmitted within a corresponding number of frames. The length of each portion may be the same, or may differ.

The label block of each frame preferably comprises encoded information concerning at least a start time and

20   routing across the network of the frame. The start time may be indicative of a delay period between an arrival time of the label block and an arrival time of the payload blocks of a frame. The start time may also be indicative of a delay period between transmission of the label block

25   of a frame, and subsequent transmission of the payload blocks of the frame.

Preferably, the delay period is selected such that the step of establishing a transparent optical path between the input port and the selected output port is completed

30   prior to arrival of the payload blocks of the frame at the

input port of the router. This allows the router to set-up the path between the input and output ports prior to arrival of the payload blocks, which can therefore be guided through the router without buffering.

5   The label block may also include an end time indicative of the location of the last bit of the data packet within the payload blocks. By this means, in cases where the packet segments are smaller than the payload blocks, the unused portion of the payload blocks can be
10 filled with predetermined stuff bits (e.g. a clock signal). The data bits of the data packet can subsequently be separated from the stuff bits by means of the end time.

        The router may include a label regenerator for regenerating the label block of the frame, and an optical
15 coupler for transmitting the regenerated label block over the label channel through the selected output port. Additionally, the router may include means for delaying the payload blocks of the frame for a predetermined period of time during passage of the payload blocks through the
20 router between the input and output ports. The predetermined period is preferably selected to preserve the start time encoded in the label block as the frame passes through the router. By this means, successive routers can be used for end-to-end transport of the frame across the
25 network.

        An advantage of the present invention is that it facilitates full optical routing of IP packets, which naturally vary widely in length, using optical routing equipment designed to accommodate fixed-length data
30 packets.

BRIEF DESCRIPTION OF THE DRAWINGS

Further features and advantages of the present invention will become apparent from the following detailed description, taken in combination with the appended drawings, in which:

Fig. 1. is a block diagram illustrating an optical communications network usable in conjunction with an embodiment of the present invention;

Figs. 2a and 2b are block diagrams illustrating an inverse multiplex frame in accordance with an embodiment of the present invention and illustrating the effect of differing propagation speeds through fiber optic media;

Fig. 3 is a block diagram schematically illustrating principal elements of an interface node of the optical communications network illustrated in Fig. 1;

Fig. 4 is a block diagram schematically illustrating principal elements of an optical router usable in the optical communications network illustrated in Fig. 1;

Fig. 5 is a block diagram schematically illustrating operation of the optical router of Fig. 4 in cases where incoming frames do not converge on a common output port; and

Fig. 5 is a block diagram schematically illustrating operation of the optical router of Fig. 4 in cases incoming frames converge on a common output port.

It will be noted that throughout the appended drawings, like features are identified by like reference numerals.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

5   The present invention provides a system for fully optical routing of variable length packetized data traffic, for example internet protocol (IP) packets and/or asynchronous transfer mode (ATM) frames across an optical network. As shown in Fig. 1, an optical network 2 usable in

10   conjunction with the present invention generally comprises a plurality of optical routers 4 (four are shown in Fig. 1) interconnected by fiber optic links 6. Communications devices 8, for example end user personal computers (PCs) or local area network (LAN) servers may be connected to the

15   optical network 2 via one or more access points 10. The optical network 2 may also be connected to one or more federated networks 12, for example an ATM or an IP network, through a respective gateway 14. Within the optical network 2, each of the optical routers 4 is configured for

20   wave division multiplex (WDM) and/or dense wave division multiplex (DWDM) transport of packet data traffic as will be described in greater detail below.

       As shown in Fig. 2a, in accordance with the present invention, packetized data is transported across the

25   optical network 2 within a frame 16 comprising a label block 18 and two or more payload blocks 20. Each block (18,20) of the frame 16 is transported across the network 2 on a respective channel (wavelength). Thus the label block 18 is transported on a respective label channel, and

30   each payload block 20 is transported on a respective

payload channel. Preferably, each of the label and payload
channels are predetermined, and remain constant across the
optical network 2, so that end-to-end transport of each of
the blocks 18,20 is effected without requiring wavelength
5   conversions.

        The label block 18 comprises encoded information
concerning the routing of the frame 16 across the network 2
and a start time (TS) of the payload blocks 20 of the
frame 16. Encoded information of an end time TE may also be
10 included in the label block 18. The routing information
may, for example, be an address on the optical network 2 of
an access point 10 serving an end-user communications
device 8, or a gateway 14 connecting the optical network 2
to an adjacent federated network 12. The encoded start time
15 (TS) is used to provide an indication of the length of a
time delay (D) between the label block 18 and the payload
blocks 20 of the frame 16. There are a variety of ways in
which the delay period (D) may be determined. For example,
it may be convenient to set the start time (TS) based on a
20 predetermined delay (D) between transmission of the first
bit of the label block 18 and transmission of the first bit
of the payload blocks 20, as shown in Fig. 2a. In this
case, as the label and payload blocks 18,20 propagate
through a link 6, differing propagation speeds of each of
25 the blocks 18,20 will cause the frame to spread. By
suitable selection of the wavelengths for each of the label
and payload channels, frame spread can be controlled such
that all of the payload blocks 20 tend to lag behind the
label block 18 as shown in Fig. 2b. In this case, at each
30 optical router 4 of the optical network 2 the start time
(TS) encoded in the label block 18 will indicate a minimum

delay period (D_{min}) between arrival of the first bit of the label block 18 and the arrival of the first bit of the first (i.e. the fastest) payload block 20a. The start time (TS) can be determined in other ways based on the selection

5   of the channel wavelengths for each of the label and payload channels and the propagation speeds of optical signals at those wavelengths. Other factors may also influence the selection of the start time (TS) and the delay period (D). In either event, the start time (TS) is

10   selected such that at each optical router 4, the label block 18 arrives at the optical router 4 a period of time prior to the payload blocks 20 sufficient to enable the label block 18 to be decoded and the optical router 4 configured (as will be described in greater detail below)

15   for routing of the payload blocks 20 prior to arrival of the first bit of the payload blocks 20 at the optical router 4.

        The end time TE is used to provide an indication of the location of the last data bit within the payload

20   blocks 20, and may, for example, take the form of a bit count of the data packet. The end time TE is of particular use in cases where the size of a data packet is less than the data capacity of the payload blocks 20. In such cases, the payload blocks 20 are only partially filed with "live"

25   data, and the remaining portion of the payload blocks 20 remains unused. In order to maintain system synchronization across the optical network 2, it may be preferable to fill the unused portion of the data blocks 20 with predetermined stuff bits (for example, a clock signal) rather than leave

30   it empty. However, when the original data packet is to be extracted from the frame 16, it becomes necessary to

separate the live data from the stuff bits. This can
readily be accomplished by means of the end time TE encoded
in the label block 18, as will be described in greater
detail below.

5   As described above and illustrated in Figs. 2a
and 2b, each of the payload blocks 20 is transmitted on its
own respective payload channel (wavelength), which is
different from the label channel used for transmission of
the label block 18. Additionally, each of the N (where N is
10   a predetermined number, and is at least 2) payload
blocks 20 has a fixed predetermined length. The length of a
data block 20 may conveniently be defined in terms of time
(or equivalently, distance) which is advantageous for
resolving issues related to buffering and/or delaying
15   payload blocks 20. The data capacity of each payload
block 20 (and thus of the frame 16 as a whole) will then be
defined as the bit rate multiplied by the payload block
length.

          The number and length of the payload blocks 20 may
20   be selected in accordance with various criteria including,
for example, an expected mean size of data packets to be
transported across the optical network 2. Selection of a
suitable combination of the number N of payload blocks 20
and the length of the payload blocks 20 can yield a highly
25   versatile data transport frame 16 which minimizes the
amount of wasted (i.e. unused) frame capacity incurred
during the transport of live data. For example, internet
protocol (IP) packets may vary in size between a few bytes
(e.g. conveying information of a mouse button click) and
30   four thousand bytes or more (e.g. conveying information of
a video image). A frame 16 may, for example, be configured

to transport 512 bytes within the payload blocks 20. In this case, an IP packet conveying information of a mouse button click would be transported within a frame 16 in which the payload blocks are mostly empty, or may contain

5   stuff bits (e.g. a clock signal). Conversely, an IP packet conveying information of a video image may be transported across the optical network 2 within several successive frames 16 each containing closely similar label information. The operation of the invention in both of

10   these cases will be described in greater detail below. In either case, for any given data capacity of a frame 16 it is possible to select between a large number N of short payload blocks 20 and a small number N of long payload blocks 20. The use of short data blocks 20 has an advantage

15   in that the data blocks 20 of the frame 16 can be processed through an optical router 4 in a comparatively short period of time, thereby reducing the probability of contention issues arising from two or more frames 16 arriving at respective input ports of the optical router 4 and destined

20   to be routed over the same outbound link for their next hop. On the other hand, the use of a large number N of payload blocks may be limited by the number of channels available for packetized data traffic, either due to physical limitations of network equipment, or due to the

25   need to provide a minimum number of channels for connection oriented traffic through the optical network 2.

Fig. 3 is a block diagram showing principal elements of an interface unit 22 which may be used in a gateway 14 or access point 12 to the optical network 2 to

30   provide conversion between conventional data packet (e.g. IP or ATM) formats and the frames 16 used for transport

across the optical network. In the illustrated embodiment,
the data packets are transported across a federated
network 12 and/or used by end user communications devices 8
as serial signals. Thus the interface unit 22 illustrated
5   in Fig. 3 generally comprises a serial-to-parallel
converter 24 which converts the serial bit stream of a data
packet into N parallel data segments. A buffer 26 is
connected to the serial-to-parallel converter 24 and is
used to store each of the N data segments. A set of N
10   optical couplers 28 are connected to the buffer 26 so that
the data segments stored within the buffer can be converted
into an optical signal having a respective unique
wavelength and launched into an optical fiber link 6. An
additional optical coupler 30 is provided for converting a
15   frame label provided by a label generator 32 into an
optical signal that is also launched into the optical fiber
link 6. A controller unit 34 is used to control operation
of the buffer 26, the label generator 32 and the optical
couplers 28,30.

20   In operation, a data packet is received as a serial
bit stream and supplied to the controller unit 34 and the
serial-to-parallel converter 24. The serial-to-parallel
converter 24 converts the serial bit stream of the data
packet into N parallel bit streams which are stored in the
25   buffer unit as data segments of the data packet. The
controller unit 34 extracts and decodes the header portion
of the data packet to determine the size (e.g. the bit
count) of the data packet and its destination address. The
controller unit 34 then controls the label generator 32 to
30   assemble a frame label containing encoded information
concerning at least routing across the optical network and

the start time (TS) of the data blocks of the frame 16. The frame label is then passed to the respective optical coupler 30 and launched over the label channel of the optical link 6 as the label block 18. The controller

5   unit 34 then controls the buffer 26 and optical couplers 28 to launch the buffered segments of the data packet as respective payload blocks 20. In cases where the size (bit count) of the data packet is less than the capacity of the frame 16, then the controller unit 34 can control the

10   buffer 26 and the optical couplers 28 to insert stuff bits (e.g. a clock signal) as necessary in order to completely fill each payload block 20. Alternatively, where the size of the data packet is greater than the capacity of the frame 16, then a first portion of each data segment can be

15   launched into the link 6 within the payload blocks 20 of a first frame, followed by a second frame 16 carrying a further (or residual) portion of the data packet. In this case, the encoded information in the label block 18 of the second frame will be closely similar to that of the first

20   frame 16, in that the routing and start time information will be identical. However, the end time TE encoded in the second (or a last) frame 16 will likely be different from that of the first frame.

The above description, with reference to the

25   embodiment of Fig. 3, describes the operation of the serial to parallel converter 24, the buffer 26, and the optical couplers 28,30 in terms of the conversion of a data packet into a frame 16 for transport across the optical network 2. It will be apparent, however, that a similar (or parallel)

30   structure may also be used to convert an incoming frame 16 into a serial data packet. In this case, the optical

couplers 28,30 may be conventional bi-directional optical couplers. The buffer 26 may also be designed to handle bi-directional data traffic, or alternatively a second buffer 36 may be employed to handle inbound frames 16. A

5   parallel-to-serial converter 38 is then used to convert the parallel packet segments into a serial bit stream and so recover a (serial) data packet from the inbound frame 16. A label decoder 40 can be provided to decode the label block 18 of the inbound frame 16, and pass the start time

10   TS and end time TE to the controller unit 34. As the recovered data packet is latched out of the parallel-to-serial converter 38, the controller unit 34 counts the number of bits. When the bit-count reaches the number of bits indicated by the end time TE encoded in the

15   label block 18 of the inbound frame 16, the controller unit 34 terminates transmission of the recovered data packet, and discards any remaining bits of the inbound frame 16.

Fig. 4 is a block diagram schematically

20   illustrating the principal elements of an optical router 4 of the optical network. In the embodiment of Fig. 4 the optical router 4 is provided with two input ports 42a,b and two output ports 42c,d. However, it will be appreciated that a greater or smaller number of ports 42 may be

25   provided in the optical router 4, and/or the optical router 4 may be provided with a plurality of ports 42 of which one or more may remain unused. It will also be appreciated that the ports 42 of the optical router may be suitably designed and connected to handle bi-directional

30   data traffic. However, in order to simplify the present description, and aid understanding of the invention, the

embodiment of Fig. 4 is provided with unidirectional ports
two of which (input ports 2a,b) are connected to handle
inbound frames, and the other two (output ports 42c,d)
connected to handle outbound frames.

5   As shown in Fig. 4, an input port 42a is connected
to receive inbound frames through a respective fiber optic
link 6a. The input port 42a generally comprises an optical
coupler 44a tuned to the label channel, and so receives the
label block 18 of an inbound frame 16. The optical
10   coupler 44a converts the label block 18 into an electrical
signal which is passed to a label decoder 46. The input
port 44a also provides a transparent optical connector 48a
designed to guide the payload blocks 20 of an inbound
frame 16 received over the data channels directly to an
15   optical switch 50, without converting the optical signals
into an electronic signal.

          The label decoder 46 receives the frame label (in
electronic form) from the optical coupler 44a and decodes
the frame label to extract the encoded routing information.
20   The routing information is then passed by the label
decoder 46 to a switch controller 52 which uses the routing
information to select one of the output ports 42c,d for
launching the frame 16 over a downstream link 6c,d for the
next hop towards the destination of the frame 16. Selection
25   of the output port may be made by known methods, for
example as defined under the MPLS protocol. In the present
example, the switch controller 52 selects the output
port 42c for the next hop. The switch controller 52 then
controls the optical switch 50, which may for example be an
30   optical space switch, to set up a transparent optical
path 54 (shown by a dashed line) between the input port 42a

and the selected output port 42c. Once the transparent
optical path 54 has been established, payload blocks 20 of
the frame 16 arriving at the input port will be conducted
across the optical router 4 to the output port 42c and

5   launched into the downstream link 6c without interruption
or conversion into electrical signals. As noted previously,
the start time (TS) is predetermined and selected so that
the delay period (D) between the launch of the first bit of
the label block 18 and the first bit of the payload

10   blocks 20 is sufficiently large to ensure that the label
block 18 of an incoming frame 16 can be converted into an
electrical signal at the input port optical coupler 44a,
decoded by the label decoder 46, and then used by the
switch controller 52 to establish the transparent optical

15   path 54 through the optical switch 50 between the input
port 42a and the selected output port 42c prior to arrival
of the first bit of the payload blocks 20 of the incoming
frame 16. The switch controller 52 can also control a label
regenerator 56 which regenerates the frame label and

20   launches a new label block 58 of the frame 16 (see Figs. 5
and 6) using an optical coupler 44c of the selected output
port 42c.

In cases where the downstream link 6c is connected
at its opposite end to an interface unit 22 such as shown

25   in Fig. 3, then preservation of the delay period (D)
between the first bit of the label block 18 and the first
bit of the payload blocks 20 of the outgoing frame 16 is
not critical. However, in general, the downstream link 6c
must be assumed to be connected at its opposite end to an

30   input port 42 of another optical router 4. In this case,
reliable transport of a frame 16 across the optical

network 2 requires that the delay period (D) must be preserved across each link. Thus the regenerated label constructed by the label regenerator 56 must be converted into an optical signal by the optical coupler 44c of the

5   selected output port 42c and launched into the downstream link 6c as a new label block 58 at least a period of time (D) prior to arrival of the first bit of the payload blocks 20 at the selected output port 6c. This can conveniently be accomplished by providing each input

10   port 42a,b with a delay loop (not shown) of a predetermined length which is sufficient to compensate for the time required to electrically convert and decode the label block 18 of the inbound frame 16, determine new routing information if required, regenerate the frame label and

15   convert the regenerated frame label into new label block 58 launched into the downstream link 6c.

As shown in Figs. 4-6 an optical router 4 may comprise two (or more) input ports 42a,b connected to respective inbound links 6a,b. In such cases it is possible

20   for respective frames 16a,b to arrive substantially simultaneously at respective input ports 42a,b of the optical router 4. Parallel decoding of the respective frame labels 18a,b within the label decoder 46 is readily possible, as is parallel set-up of transparent optical

25   paths 54a,b through the optical switch under the control of the switch controller. As shown in Fig. 5, if the routing information encoded in the respective frame labels 18a,b is such that the transparent optical paths 54a,b are set up through the optical switch to respective different output

30   ports 42c,d then the payload blocks 20a,b of each frame 16a,b can be conducted through the optical router 4

and launched into their respective downstream links 6c,d without difficulty. However, as shown in Fig. 6, if the routing information encoded in the respective frame labels 18a,b requires transparent optical guide paths to be

5   established across the optical switch to a common output port 42c, the resulting contention between the inbound frames 16a,b must be resolved in order to prevent destructive interference of the inbound frames 10a,b. As mentioned previously, the use of comparatively short

10   payload blocks 20 minimizes the probability of contention issues arising, by reducing the likelihood that frames 16a,b may arrive at different input ports 42a,b at the same time (or close enough in time that the respective sets of payload blocks 20a,b would overlap upon convergence

15   of the two frames 16a,b into the downstream link 6c). An added measure of reliability can also be obtained by providing a delay loop 60 within the router 4. Thus, in the event of frame contention, one of the transparent optical paths 54b can be routed through the optical switch 50 in

20   such a way as to incorporate the delay loop 60. The delay loop 60 can conveniently be sized to impose a delay of a predetermined length, such as for example an integer multiple of the payload block length. Thus in the case of contending frames 16a,b arriving at respective input

25   ports 42a,b, the payload blocks 20b of one of the contending frames 16b will be delayed by the delay loop 60 for a time sufficient to permit the payload blocks 20a of the other frame 16a to clear the router 4 and be launched into the downstream link 6c. Because the payload blocks 20

30   of each frame 16 are a predetermined fixed length, this operation can reliably be performed even when the data packets being transported within each frame 16a,b are of

different length. Thus it will be seen that the present
invention facilitates full optical routing of variable
length data packets.

        The embodiment(s) of the invention described above
5   is(are) intended to be exemplary only.   The scope of the
invention is therefore intended to be limited solely by the
scope of the appended claims.